

Application for Septic Tanks

Sewer line Application:

Also for root problems from the sewer line going from the house then apply RootX through the toilet or a clean out. For complete directions refer to directions for use located on the jar label.

Septic Tank Application:

To apply RootX to a septic tank you want to pump the tank down below the root intrusion. Then apply RootX to the tank and spray with water to help agitate the foaming action. If it is possible to apply RootX onto the root directly then spray the roots, cleaning them and wetting them with water. Then apply the RootX on the root system adding water to activate the foaming action. When treating the sewer line going from the tank to the distribution box RootX has to be applied through a cleanout near the tank. If there is no cleanout then one needs to be installed in order for the application to be successful.

Drain Field Application:

If the root problem is in the drain field then apply RootX to the distribution box. **Do not apply RootX to the septic tank to treat the drain field**. With the drain field typically being perforated pipe results may very and RootX is not guaranteed with this application.

Application Rates For Septic Tank:

- 1-4lb. Jar treats approximately 500 Gallon Septic Tank
- 2-4lb Jar treats approximately 1000 Gallon Septic Tank
- 3-4lb jar treats approximately 1500 Gallon Septic Tank

Application Rates For Drain Field:

- 1-2lb. Jar treats approximately 50 feet of 4-inch pipe.
- 1-4lb. Jar treats approximately 100 feet of 4-inch pipe.
- 1-4lb. Jar treats approximately 75 feet of 6-inch pipe.

Call (800) 844-4974 or visit us at www.rootx.com